

YTX4L-Na

Voltage: 12V

Capacity: 2.2AH

CCA: 150 A



Specification:

Cell	Rated Voltage/Capacity	3.0V/1100mAh
Electrical Characteristics	Nominal Voltage	12V
	Nominal Capacity	2.2Ah
	Energy	26.4Wh
	Internal Resistance	≤35mΩ
	Cycle Life	>3000 cycles @1C 70%DOD
	Efficiency of Discharge	96~99% @1C
Charge	Charge Voltage	15.8V±0.2V
	Charge Current	2.2A
	Max. Charge Current	6.6A
Discharge	Continuous Current	70A
	Max. Pulse Current	150A 3S@100% SOC 10V @50% SOC 6V
Environmental	Charge Temperature	0 °C to 45 @60± 25% Relative Humidity
	Discharge Temperature	(-40 °C to 60 °C) @60 ±25% Relative Humidity
	Storage Temperature	(-10 °C to 40 °C)@60 ±25% Relative Humidity
	Water Dust Resistance	IP67
Mechanical	Plastic Case	ABS
	Dimensions (mm)	113x69x86mm±5mm
	Weight(kg)	0.5kg

Safety warning

In order to prevent battery leakage, heat, explosion, please observe the following precautions:

- Don't put battery into water or seawater, note moist
- Don't the battery near heat sources, such as fire or heater When charging, please use the specific charger
- Don't reverse battery is negative
- Do not connect the battery in the power of export
- Do not place the battery in fire or hot items
- Don't across the electrodes of the battery short circuit conductors
- Don't put the battery and the metal conductor, such as necklace, hairpin, etc connected or stored together
- Do not knock or throw the battery
- Don't Pierce the battery with pin or other sharp
- Don't use hammer strike or step on the top
- Don't direct welding power source