


marvel[®] Tech

MIS III TWIN



▶ 1. Dual outputs for smart load management

There are two outputs available, The second output can be scheduled on/off, setting cut-off voltage or SOC and discharging time via LCD setting, It facilitates users smart load control.

▶ 2. Maximum PV input current 27A

Designed with 27A PV input current, MIS III TWIN is compatible to the market trend of increased Imp in solar panel.

▶ 3. Wide PV input voltage range 60VDC ~ 450VDC

Now, Ouyad MIS III TWIN allows wide PV input voltage range from 60VDC to 450VDC, This features allow less solar panel required in the system and save space.

▶ 4. Detachable LCD control module with various communications

This detachable LCD control module can be turned to remote panel. Users can install the LCD panel in accessible area away from inverter up to 20 meters.

▶ 5. Integrated WiFi interface with Mobile App

MIS III TWIN series is integrated WiFi interface ready for mobile monitoring, Mobile monitoring can be carried out through mobile applications in both iOS and Android, Users can track the history of the unit information such as energy generation and change parameter settings timely.



▶ 7. Reserved communication port (RS-485, CAN-BUS or RS-232) for BMS

This third generation inverter is reserved communication port for BMS. For the detailed information, please contact sales directly.

▶ 8. Battery equalization extends lifecycle

This inverter charger is built in battery equalization function. This function will help remove sulfation to optimize battery performance and even extend lifecycle.

▶ 9. Battery independency

Inverter can keep supplying power to the loads from PV energy or the grid without battery connected.



▶ 6. Supports USB On-the-Go function

MIS III TWIN series supports USB On-the-Go function to facilitate data upload/download.



▶ 10. User-friendly LCD operation

Users can easily set up or change the charging current, output source and charger source prioritization through LCD control panel to optimize inverter performance.



▶ 11. Replaceable fan design

MIS III TWIN series is designed with replaceable fan, It will simplify the maintenance and reduce the maintenance cost.

marvel[®] Tech

MIS III TWIN

Technical Specifications:

Model	MIS III 4K TWIN	MIS III 6K TWIN
Rated Power	4000VA/4000W	6000VA/6000W
INPUT		
Voltage	230 VAC	
Selectable Voltage Range	170-280VAC (For Personal Computers), 90-280VAC (For Home Appliances)	
Frequency	50Hz/60Hz(Auto Sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	230VAC \pm 10%	
Surge Power	8000VA	12000VA
Efficiency (Peak)	90%-93%	
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC
Overcharge Protection	33 VDC	63 VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	MPPT
Maximum PV Array Power	5000W	6000W
MPPT Range @operating Voltage	60~450VDC	
Max. PV Array Open Circuit Voltage	500VDC	
Max. Solar Charge Current	120A	120A
Max AC Charge Current	100A	100A
Max Charge Current	120A	120A
PHYSICAL		
Dimension, D x W x H(mm)	115 x 300 x 435	
Net Weight(kgs)	9kg	10kg
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact	
OPERATING ENVIRONMENT		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
Operating Temperature	-10° C to 50° C	
Storage Temperature	-15° C-60° C	